

Status of Scenario Generation Task

Scenario Metrics

Presented By Scott Summerill

September 29, 1999





Scenario Metrics Overview

- Provide review of scenario metrics being developed
- Metrics defined in Description of Accuracy Scenarios for the Acceptance Testing of URET CCLD, Review Draft 9/14/99
- Results based on preliminary scenarios
 - proof of concept only
- Two preliminary scenarios for calculating results
 - Five hour modestly time shifted ZME scenario from 5/26/99
 - Ten hour ZME scenario from 5/26/99 (not time shifted)





List of Areas used to Generate Scenario Metrics

- Center Airspace ✓
- Encounters ✓
- Air Traffic ✓
- Aircraft ✓
- Interfacility Traffic Flow
- Flight Plan Adherence
- Weather Forecasts





Center Airspace

Defining Characteristics

- Airports
- Sectors
- Airways
- Preferential Routes
- Special Use Airspace
- Terminal Areas (APDIA)
- Fix Posting Areas

Metrics

- Total Count





Encounter Distributions

- Aircraft to Aircraft Encounters
- Aircraft to Airspace Encounters



SS-5



Encounter Distributions

Aircraft to Aircraft Encounters

 Tracks of aircraft pairs within 30 nm and violate standard vertical thresholds

Metrics

- Count of Encounters partitioned by Minimum Horizontal Separation Intervals
- Count by Altitude Interval
- Count by Encounter Angle and Vertical Phase of Flight





Counts of Aircraft to Aircraft Encounters

Minimum Horizontal Separation (nm)	Number of Encounters
0 <= d < 5	200
5 <= d < 10	198
10 <= d < 15	280
15 <= d < 23	527
23 <= d < 30	486
Total	1691





Count by Phase of Flight and Encounter Angle

Vertical	Encounter Angles (degrees)			
Phase of Flight	[0,45)	[45,90)	[90,135)	[135,180]
Cruise-Cruise	81	110	69	37
Descend-Descend	60	24	11	13
Climb-Climb	40	11	5	11
Unknown	15	0	2	1
Cruise-Climb	139	91	88	146
Cruise-Descend	182	122	103	156
Climb-Descend	52	20	29	73





Encounter Distributions

Aircraft to Airspace Encounters

- Track of aircraft within 30 nm of Special Use Airspace

Metrics

- Count of Encounters partitioned by Minimum Horizontal Separation Intervals
- Count by Altitude Intervals
- Count by Encounter Angle and Vertical Phase of Flight





Counts of Aircraft to Airspace Encounters

Minimum Horizontal Separation (nm)	Number of Encounters
0 <= d < 7	1725
7 <= d < 9	134
9 <= d < 11	151
11 <= d < 16	444
16 <= d < 30	1278
Total	3632





- Air Traffic Density
- Active Flights
- Flight Type & Sector Penetration
- Aircraft Ground Speed
- Flight Life
- Center to APD Ratio
- Center Boundary Activity
- Aircraft Maneuvers





Air Traffic Density

- Minimum horizontal separation partitioned by altitude and time
- 1000/2000 foot vertical partitions
- One hour segments

Metrics


- Mean
- Variance



SS-12



Average Hourly Minimum Horizontal Separation by Altitude







Active Flights

Measure of the number of flights operating in center by time


Metrics

- Total count
- Count by minute





Count of Flights by Minute



Statistics for 5 hour sample ZME without FP adherence



Figure B.2-1 SS-15



Flight Type and Sector Penetration

- Distribution of flight type by number of sectors penetrated and time duration
- ARR, DEP, OVR, INR


Metrics

- Average sectors penetrated by flight type
- Average time in sector
- Average time in center
- Percentage in center by flight type






Average Number of Sectors Penetrated by Flight Type








Average Time in Sector by Flight Type








Average Time in Center by Flight Type







Percentage of Flights by Flight Type







Ground Speed

 Flight ground speed partitioned by standard altitude intervals

Metrics


- Mean
- Variance



SS-21



Average Ground Speed by Altitude



Statistics for 5 hour sample ZME without FP adherence



Figure B.4-1 SS-22



Flight Life

Measure of the average time duration of a track in center

Metrics

- Mean
- Std Deviation

Results

- Mean 35.25 minutes

- Std Dev 19.62 minutes





Center to APD Ratio

 Ratio of track reports for flights within center to total HCS track reports (center + APD zone)

Metrics

Ratio or Percent

Results

- TBD



SS-24



Center Boundary Activity

- Rate of flight entering and leaving center airspace
- Measure of flight activity crossing center boundary

Metrics

- Count per unit time

Results





Interim Altitude Messages

- Interim Altitude Messages per Flight

Metrics

Count per unit time

Results





Air Traffic Maneuvers

- Turns by altitude interval
- Ascents and descents by altitude interval

Metrics

- Total Count

Results





Aircraft Distributions

- Aircraft Type
- Aircraft Model
- Navigation Equipage
- Carrier





Aircraft Distributions

Aircraft Type Distribution

- Distribution of all aircraft operating in center by type classification
- Piston, Turboprop, Jet, Helicopter


Metrics

- Total Count
- Percent Total





Distribution of Aircraft by Type







Aircraft Distributions

Aircraft Models Distribution

- Distribution of aircraft operating in center classified by model type
- DC9, B733, etc.

Metrics


- Total Count
- Percent Total



SS-31



Distribution of Aircraft by Model - Top Ten -







Aircraft Distributions

Navigation Equipage

- Distribution of navigational equipment aboard aircraft operating in center airspace
- Classified as A, I, G, etc.


Metrics

- Total Count
- Percent Total





Distribution of Navigation Equipage







Aircraft Distributions

Carrier Distribution

- Distribution of carriers operating in center airspace
- DAL for Delta Airlines, etc.


Metrics

- Total Count
- Percentage Total





Air Carrier Distribution - Top Ten -







Flight Plan Adherence

- Lateral Flight Plan Adherence
- Vertical Flight Plan Adherence



SS-37



Flight Plan Adherence

Lateral Flight Plan Adherence

 Measure of aircraft lateral deviation from track report to converted route

Metrics

- Average Delta (nautical miles)
- Std Deviation
- Max and Minimum

Results





Flight Plan Adherence

Vertical Flight Plan Adherence

Vertical deviation from track reported altitude to assigned altitude

Metrics

- Average Delta (feet)
- Std Deviation
- Max and Minimum

Results





Interfacility Traffic Flow

Definition

Rate of aircraft flying between facilities

ZID to ZME ZME to ZID

Other to ZME ZME to Other

Metrics

- Count per Hour
- Average
- Std Deviation
- Max and Minimum

Results





Weather Variations

- Variation
- Time Shifting Effect



SS-41



Weather Variations

Variation

- Change in wind speed and direction over time
- Change in temperature over time

Metrics

- Average
- Std Deviation
- Median
- Range

Results

- TBD



Section 3.7.1 SS-42



Weather Variations

Time Shifting Effect

Comparison of trajectory accuracy with and without time shifting

Metrics

 Difference in accuracy as defined in *Trajectory Prediction Accuracy Report: URET/CTAS,* (DOT/FAA/CT-TN99/10)

Results





Next Steps

- Complete Metrics
- Apply smoothing technique for Phase of Flight
- Assist with WARP1 conversion





Some Accuracy Scenario Risk Areas

CMS Format Conversion

- Cause: CMS IRD is moving target with continuous stream of RPRs and lack of a definition of the file required for accuracy
- Mitigation:
 - » develop close relationship with LMATM by working on new SIG 264 to define the CMS-formatted scenario
 - » provide preliminary CMS-formatted scenario messages to LMATM for verification with their tools

RUC 236 WARP1 Conversion

- Cause: dependent on shareware, etc.
- Mitigation:
 - » work with AST for early date test run (~Feb. or March 2000)
 - » LMATM help?
 - » MITRE help?





Some Accuracy Scenario Risk Areas Cont'd

- Meeting Encounter Constraints With Flight Adherence
 - Cause: dealing with real traffic and limited sample data
 - Mitigation:
 - » time shifting and backup method of cloning
 - » we can set lateral deviation thresholds accordingly (vertical is already defined in SSD)
- Trajectory Accuracy Degradation from Time Shifting
 - Cause: weather data may not be time synchronized due to time shifting of flights
 - Mitigation:
 - » specification refresh will level the playing field
 - » perform brief trajectory accuracy comparison to original field data

